

Description

Diameter: 3/16", Grip Length: 3/8", flush head, ms20426, aluminum alloy, anodized, HL23 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL2366
Minimum Qty (MOQ):	5
NSN:	5320-00-421-0078
Schedule B:	7616.99.5090
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N HL23-6-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.690 Inches Minimum And 0.710 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.079 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.349 Inches Minimum And 0.354 Inches Maximum
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Nominal Thread Size:	0.190 Inches
Countersink Angle:	100.0 Degrees Nominal
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-225/9 Fed Spec Single Material Response Or Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL23-6-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.