

**Description**

100°, flush ms20426 shear head - aluminum alloy - anodized

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL2367
Minimum Qty (MOQ):	1
NSN:	5320-00-246-0374
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

## P/N HL23-6-7 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.753 Inches Minimum And 0.773 Inches Maximum
<b>Head Style:</b>	Flush Countersunk
<b>Width Between Flats:</b>	0.079 Inches Minimum And 0.081 Inches Maximum
<b>Shank Diameter:</b>	0.189 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.349 Inches Minimum And 0.354 Inches Maximum
<b>Grip Length:</b>	0.443 Inches Maximum
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Heat Treatment:</b>	T-6 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 7075 Overall
<b>Material Document And Classification:</b>	Qq-a-225/9 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL23-6-7](https://military-fasteners.com/rivets/pin_rivets/HL23-6-7) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.