

Description

100°, flush ms20426 shear head - aluminum alloy - anodized

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL2368
Minimum Qty (MOQ):	1
NSN:	5320-01-205-8030
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N HL23-6-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.815 Inches Minimum And 0.835 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.079 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.189 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.349 Inches Minimum And 0.354 Inches Maximum
Grip Length:	0.496 Inches Nominal
Nominal Thread Size:	0.190 Inches
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-225/9 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL23-6-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.