

Description

100°, flush ms20426 shear head - aluminum alloy - anodized

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL2369
Minimum Qty (MOQ):	1
NSN:	5320-00-438-9511
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N HL23-6-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.877 Inches Minimum And 0.897 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.3486 Inches Minimum And 0.3536 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.557 Inches Minimum And 0.567 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Countersink Angle:	100.0 Degrees Nominal
Criticality Code Justification:	Aatb And Aaze And Aazg
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-430 Fed Spec 1st Material Response Overall Or Qq-a-225/9 Fed Spec 2nd Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL23-6-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.