

Description

Fastener Length: 1-3/16", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL301011
Minimum Qty (MOQ):	1 EA
NSN:	5320-00-797-1439
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

P/N HL30-10-11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.178 Inches Minimum And 1.198 Inches Maximum
Head Style:	Err-090
Head Height:	0.068 Inches Minimum And 0.078 Inches Maximum
Width Between Flats:	0.127 Inches Minimum And 0.130 Inches Maximum
Shank Diameter:	0.311 Inches Minimum And 0.312 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.475 Inches Minimum And 0.505 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.683 Inches Minimum And 0.693 Inches Maximum
Nominal Thread Size:	0.312 Inches
Shear Strength:	19160 Double Pounds Per Square Inch
Material:	Steel Comp 431 Overall
Material Document And Classification:	Mil-s-18732 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	258,fscm 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL30-10-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.