

## Description

Fastener Length: 1-1/4", Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | HL301012                                    |
| Minimum Qty (MOQ):      | 5 EA  |
| NSN:                    | 5320-00-797-1438                            |
| Schedule B:             | 7318.24.0000                                |
| ECCN:                   | 9A991                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N HL30-10-12 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Fastener Length:</b>                               | 1.240 Inches Minimum And 1.260 Inches Maximum            |
| <b>Head Style:</b>                                    | Err-090  |
| <b>Head Height:</b>                                   | 0.068 Inches Minimum And 0.078 Inches Maximum            |
| <b>Width Between Flats:</b>                           | 0.127 Inches Minimum And 0.130 Inches Maximum            |
| <b>Shank Diameter:</b>                                | 0.311 Inches Minimum And 0.312 Inches Maximum            |
| <b>Shank Style:</b>                                   | Pin-rivet, Straight, Threaded                            |
| <b>Head Major Diameter:</b>                           | 0.475 Inches Minimum And 0.505 Inches Maximum            |
| <b>Lubrication:</b>                                   | Cetyl Alcohol  |
| <b>Grip Length:</b>                                   | 0.745 Inches Minimum And 0.755 Inches Maximum            |
| <b>Nominal Thread Size:</b>                           | 0.312 Inches   |
| <b>Shear Strength:</b>                                | 19160 Double Pounds Per Square Inch                      |
| <b>Material:</b>                                      | Steel Comp 431 Overall                                   |
| <b>Material Document And Classification:</b>          | Mil-s-18732 Mil Spec Single Material Response Overall    |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | 258,fscm 73197 Mfr Ref Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this hl pin from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL30-10-12](https://military-fasteners.com/pins/pin_rivets/HL30-10-12) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.