

Description

protruding shear head - 431 stainless steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL30106
Minimum Qty (MOQ):	1
NSN:	5320-00-797-1478
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N HL30-10-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Head Style:	Err-090
Head Height:	0.068 Inches Minimum And 0.078 Inches Maximum
Width Between Flats:	0.127 Inches Minimum And 0.130 Inches Maximum
Shank Diameter:	0.311 Inches Minimum And 0.312 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.475 Inches Minimum And 0.505 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.370 Inches Minimum And 0.380 Inches Maximum
Nominal Thread Size:	0.312 Inches
Shear Strength:	19160 Double Pounds Per Square Inch
Material:	Steel Comp 431 Overall
Material Document And Classification:	Mil-s-18732 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	258,fscm 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL30-10-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.