

Description

protruding shear head, stainless steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL3053
Minimum Qty (MOQ):	5
NSN:	5320-01-581-5709
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N HL30-5-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Countersunk W/reverse Chamfer
Head Height:	0.037 Inches Minimum And 0.047 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.080 Inches Maximum
Shank Diameter:	0.162 Inches Minimum And 0.163 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.242 Inches Minimum And 0.262 Inches Maximum
Grip Length:	0.183 Inches Minimum And 0.193 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Shear Strength:	125000 Single Pounds Per Square Inch
Countersink Angle:	90.0 Degrees Minimum And 100.0 Degrees Maximum
Material:	Steel Comp 431 Overall
Material Document And Classification:	Ams 5828 Assn Std Single Material Response Overall Or Mil-s-18732 Mil Spec Single Material Response Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL30-5-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.