

Description

Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL30611
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-935-9069
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N HL30-6-11 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	1.003 Inches Minimum And 1.023 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.045 Inches Minimum And 0.055 Inches Maximum
<b>Width Between Flats:</b>	0.079 Inches Minimum And 0.081 Inches Maximum
<b>Shank Diameter:</b>	0.189 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.295 Inches Minimum And 0.315 Inches Maximum
<b>Grip Length:</b>	0.683 Inches Minimum And 0.693 Inches Maximum
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Shear Strength:</b>	125000 Single Pounds Per Square Inch
<b>Material:</b>	Steel Comp 431 Overall
<b>Material Document And Classification:</b>	Mil-s-18732 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	258,fscm 73197 Mfr Ref Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this hl pin from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL30-6-11](https://military-fasteners.com/pins/pin_rivets/HL30-6-11) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.