

**Description**

Diameter: 3/16", Grip Length: 3/16", protruding shear head, stainless steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL3063
Minimum Qty (MOQ):	10
NSN:	5320-00-797-1508
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N HL30-6-3 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.503 Inches Minimum And 0.523 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.045 Inches Minimum And 0.055 Inches Maximum
<b>Width Between Flats:</b>	0.079 Inches Minimum And 0.081 Inches Maximum
<b>Shank Diameter:</b>	0.189 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.295 Inches Minimum And 0.315 Inches Maximum
<b>Grip Length:</b>	0.183 Inches Minimum And 0.193 Inches Maximum
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Shear Strength:</b>	7060 Double Pounds Per Square Inch
<b>Special Features:</b>	Centyl Alcohol Lubrication
<b>Material:</b>	Steel Comp 431 Overall
<b>Material Document And Classification:</b>	Mil-s-18732 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	258,fscm 73197 Mfr Ref Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL30-6-3](https://military-fasteners.com/pins/pin_rivets/HL30-6-3) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.