

Description

Fastener Length: 7/16", Thread Size: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL3152
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-256-7699
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N HL31-5-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.427 Inches Minimum And 0.447 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.079 Inches Minimum And 0.080 Inches Maximum
Shank Diameter:	0.163 Inches Minimum And 0.164 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.256 Inches Minimum And 0.261 Inches Maximum
Grip Length:	0.130 Inches Maximum
Nominal Thread Size:	0.164 Inches
Shear Strength:	125000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp 431 Overall
Material Document And Classification:	Mil-s-18732 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	258,fscm 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL31-5-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.