

Description

Fastener Length: 1/16", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | HL3188 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-527-4260 |



P/N HL31-8-8 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.0895 Inches Maximum |
| Head Style: | Flush Countersunk |
| Width Between Flats: | 0.122 Inches Minimum And 0.142 Inches Maximum |
| Shank Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.3898 Inches Minimum And 0.3948 Inches Maximum |
| Lubrication: | Cetyl Alcohol |
| Grip Length: | 0.395 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.250 Inches |
| Shear Strength: | 12260 Double Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Steel Comp 431 Overall |
| Material Document And Classification: | Ams5628 Assn Std Single Material Response Overall Or Mil-s-18732 Mil Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL31-8-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.