

## P/N HL31-8-8

### **Description**

Fastener Length: 1/16", Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: HL3188
Minimum Qty (MOQ): 10

NSN: 5320-01-527-4260



# **P/N HL31-8-8 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.0895 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.122 Inches Minimum And 0.142 Inches Maximum
Shank Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.3898 Inches Minimum And 0.3948 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.395 Inches Nominal
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Shear Strength:	12260 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp 431 Overall
Material Document And Classification:	Ams5628 Assn Std Single Material Response Overall Or Mil-s-18732 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this pin-rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/pin\_rivets/HL31-8-8">https://military-fasteners.com/rivets/pin\_rivets/HL31-8-8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/pin\_rivets/HL31-8-8">https://military-fasteners.com/rivets/pin\_rivets/HL31-8-8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/pin\_rivets/HL31-8-8">https://military-fasteners.com/rivets/pin\_rivets/HL31-8-8</a> and selecting the quantity you want then click "add to cart".