

Description

Diameter: 5/32", Grip Length: 1/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL32652
Minimum Qty (MOQ):	10
NSN:	5320-01-006-9079
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N HL326-5-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.427 Inches Minimum And 0.447 Inches Maximum
Head Style:	Err-090
Head Height:	0.055 Inches Minimum And 0.060 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.080 Inches Maximum
Shank Diameter:	0.1635 Inches Minimum And 0.1650 Inches Maximum
Shank Style:	Pin-rievet, Straight, Threaded
Head Major Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Grip Length:	0.130 Inches Maximum
Thread Quantity Per Inch:	36
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.164 Inches
Shear Strength:	4010 Double Pounds Per Square Inch
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rievet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL326-5-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.