

**Description**

protruding tension head alloy steel interference application cadmium plated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL32664
Minimum Qty (MOQ):	10
NSN:	5320-00-137-6733
National Motor Freight:	095190, Hardware, Noi

NO IMAGE  
AVAILABLE

## P/N HL326-6-4 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.565 Inches Minimum And 0.585 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.064 Inches Minimum And 0.074 Inches Maximum
<b>Width Between Flats:</b>	0.079 Inches Minimum And 0.081 Inches Maximum
<b>Shank Diameter:</b>	0.1880 Inches Minimum And 0.1895 Inches Maximum
<b>Head Major Diameter:</b>	0.357 Inches Minimum And 0.377 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.255 Inches Maximum
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Shear Strength:</b>	160000 Single Pounds Per Square Inch
<b>Material:</b>	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall
<b>Material Document And Classification:</b>	Mil-s-5000 Fed Spec 1st Material Response Overall Or Mil-s-6249 Fed Spec 2nd Material Response Overall Or Mil-s-5626 Fed Spec 3rd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL326-6-4](https://military-fasteners.com/rivets/pin_rivets/HL326-6-4) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.