

Description

Fastener Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | HL32684 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5320-01-581-2510 |
| Schedule B: | 7318.24.0000 |
| ECCN: | 9A991 |

NO IMAGE
AVAILABLE

P/N HL326-8-4 Specifications

| | |
|---|--|
| Fastener Length: | 0.395 Inches Maximum |
| Width Between Flats: | 0.122 Inches Minimum And 0.142 Inches Maximum |
| Shank Diameter: | 0.415 Inches Minimum And 0.440 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Grip Length: | 0.250 Inches Maximum |
| Part Name Assigned By Controlling Agency: | Protruding Tension Head |
| Material: | Steel Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec Single Material Response Overall Or Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall |

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL326-8-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.