

**Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL32859
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-581-2525
Schedule B:	7318.24.0000
ECCN:	9A991



## P/N HL328-5-9 Specifications

<b>Fastener Length:</b>	0.312 Inches Maximum
<b>Width Between Flats:</b>	0.094 Inches Minimum And 0.104 Inches Maximum
<b>Shank Diameter:</b>	0.242 Inches Minimum And 0.262 Inches Maximum
<b>Shank Style:</b>	Pin-riquet, Straight, Threaded
<b>Grip Length:</b>	0.562 Inches Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Protruding Tension Head
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Mil-s-5000 Mil Spec Single Material Response Overall Or Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL328-5-9](https://military-fasteners.com/rivets/pin_rivets/HL328-5-9) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.