

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL32859
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-581-2525
Schedule B:	7318.24.0000
ECCN:	9A991



* See page 2 for technical characteristics

P/N HL328-5-9 Specifications

Fastener Length:	0.312 Inches Maximum
Width Between Flats:	0.094 Inches Minimum And 0.104 Inches Maximum
Shank Diameter:	0.242 Inches Minimum And 0.262 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Grip Length:	0.562 Inches Maximum
Part Name Assigned By Controlling Agency:	Protruding Tension Head
Material:	Steel Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Overall Or Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL328-5-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.