

Description

protruding shear head - alloy steel interference application cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL32863
Minimum Qty (MOQ):	10
NSN:	5320-01-286-5474
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N HL328-6-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.503 Inches Minimum And 0.523 Inches Maximum
Head Style:	Err-090
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Head Major Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.193 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Shear Strength:	108000 Single Pounds Per Square Inch
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rievet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL328-6-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.