

**Description**

Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | HL32958          |
| Minimum Qty (MOQ): | 25 EA            |
| NSN:               | 5320-01-581-3977 |
| Schedule B:        | 7318.24.0000     |
| ECCN:              | EAR99            |

NO IMAGE  
AVAILABLE

## P/N HL329-5-8 Specifications

|   |   |
|---|---|
| <b>Head Style:</b>                                    | Flush Countersunk   |
| <b>Shank Diameter:</b>                                | 0.164 Inches Minimum And 0.165 Inches Maximum                     |
| <b>Shank Style:</b>                                   | Stump   |
| <b>Head Major Diameter:</b>                           | 0.256 Inches Minimum And 0.261 Inches Maximum                     |
| <b>Grip Length:</b>                                   | 0.500 Inches Nominal  |
| <b>Countersink Angle:</b>                             | 100.0 Degrees Nominal   |
| <b>Part Name Assigned By Controlling Agency:</b>      | Hi-lock Threaded Fastening System                                 |
| <b>Material:</b>                                      | Steel Overall   |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2,class 2 Mfr Ref Single Treatment Response Overall |

## How to Order

Order this rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL329-5-8](https://military-fasteners.com/rivets/pin_rivets/HL329-5-8) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.