

**Description**

Fastener Length: 29/64", Thread Size: 3/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL32962
Minimum Qty (MOQ):	15 EA
NSN:	5320-00-448-8320
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE  
AVAILABLE

## P/N HL329-6-2 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.440 Inches Minimum And 0.460 Inches Maximum
<b>Head Style:</b>	Flush Countersunk
<b>Width Between Flats:</b>	0.079 Inches Minimum And 0.081 Inches Maximum
<b>Shank Diameter:</b>	0.188 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.297 Inches Minimum And 0.302 Inches Maximum
<b>Grip Length:</b>	0.130 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Shear Strength:</b>	108000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL329-6-2](https://military-fasteners.com/rivets/pin_rivets/HL329-6-2) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.