

Description

Fastener Length: 53/64", Thread Size: 3/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL32968
Minimum Qty (MOQ):	10
NSN:	5320-01-454-0490
Schedule B:	7318.24.0000
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N HL329-6-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.815 Inches Minimum And 0.835 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.2956 Inches Minimum And 0.3016 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.495 Inches Minimum And 0.505 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Shear Strength:	108000 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Overall Or Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL329-6-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.