

Description

Fastener Length: 37/64", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL32983
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-458-4484
Schedule B:	7318.24.0000
ECCN:	EAR99



* See page 2 for technical characteristics

P/N HL329-8-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.572 Inches Minimum And 0.592 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0947 Inches Minimum And 0.0967 Inches Maximum
Shank Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.3898 Inches Minimum And 0.3948 Inches Maximum
Grip Length:	0.187 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Thread Series Designator:	Unjf

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL329-8-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.