

**Description**

HL32PB8-12 Pin-Rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL32PB812
Minimum Qty (MOQ):	1
NSN:	5320-00-527-5476
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE  
AVAILABLE

## P/N HL32PB8-12 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	1.135 Inches Minimum And 1.155 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Width Between Flats:</b>	0.0947 Inches Minimum And 0.0967 Inches Maximum
<b>Shank Diameter:</b>	0.2485 Inches Minimum And 0.2495 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.415 Inches Minimum And 0.440 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.755 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Shear Strength:</b>	125000 Single Pounds Per Square Inch
<b>Special Features:</b>	Cetyl Alcohol Lubrication
<b>Material:</b>	Steel Comp 431 Overall
<b>Material Document And Classification:</b>	Ams 5628 Assn Std Single Material Response Overall Or Mil-s-18732,ty 431 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL32PB8-12](https://military-fasteners.com/pins/pin_rivets/HL32PB8-12) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.