



Military-Fasteners.com

P/N HL32PB8-12

Description

HL32PB8-12 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL32PB812
Minimum Qty (MOQ):	1
NSN:	5320-00-527-5476
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N HL32PB8-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.135 Inches Minimum And 1.155 Inches Maximum
Head Style:	Err-090
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Width Between Flats:	0.0947 Inches Minimum And 0.0967 Inches Maximum
Shank Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.415 Inches Minimum And 0.440 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.755 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Shear Strength:	125000 Single Pounds Per Square Inch
Special Features:	Cetyl Alcohol Lubrication
Material:	Steel Comp 431 Overall
Material Document And Classification:	Ams 5628 Assn Std Single Material Response Overall Or Mil-s-18732,ty 431 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL32PB8-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.