

Description

Fastener Length: 13/16", Thread Size: 5/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL40105
Minimum Qty (MOQ):	5
NSN:	5320-01-254-2594
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N HL40-10-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Head Style:	Err-090
Head Height:	0.068 Inches Minimum And 0.078 Inches Maximum
Width Between Flats:	0.1270 Inches Minimum And 0.1295 Inches Maximum
Shank Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Shank Style:	Pin-riivet, Straight, Threaded
Head Major Diameter:	0.475 Inches Minimum And 0.505 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.317 Inches Maximum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.312 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall Or Ams 5731 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-riivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL40-10-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.