

Description

Fastener Length: 1-17/32", Thread Size: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL401216
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-104-9215
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N HL40-12-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.545 Inches Nominal
Head Style:	Err-090
Head Height:	0.078 Inches Minimum And 0.088 Inches Maximum
Width Between Flats:	0.1582 Inches Minimum And 0.1617 Inches Maximum
Shank Diameter:	0.3740 Inches Minimum And 0.3745 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.565 Inches Minimum And 0.600 Inches Maximum
Grip Length:	1.000 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	8700 Pounds Per Square Inch
Nominal Thread Size:	0.375 Inches
Shear Strength:	21000 Double Pounds Per Square Inch
Criticality Code Justification:	Aaze And Aatb
Material:	Steel Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL40-12-16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.