

**Description**

Fastener Length: 1-21/32", Thread Size: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL401218
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-105-0569
Schedule B:	7318.16.0060
ECCN:	EAR99
National Motor Freight:	105000, Dowel Pins I / S Noi In Bag / Bbl / Boxes

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N HL40-12-18 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	1.670 Inches Nominal
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.078 Inches Minimum And 0.088 Inches Maximum
<b>Width Between Flats:</b>	0.1582 Inches Minimum And 0.1617 Inches Maximum
<b>Shank Diameter:</b>	0.3740 Inches Minimum And 0.3745 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.565 Inches Minimum And 0.600 Inches Maximum
<b>Grip Length:</b>	1.125 Inches Nominal
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	8700 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.375 Inches
<b>Shear Strength:</b>	21000 Double Pounds Per Square Inch
<b>Criticality Code Justification:</b>	Aaze And Aatb
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL40-12-18](https://military-fasteners.com/rivets/pin_rivets/HL40-12-18) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.