

Description

protruding shear head, high temperature alloy, passivated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | HL4042 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5320-01-533-1097 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N HL40-4-2 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.419 Inches Nominal |
| Head Style: | Straight Pan |
| Head Height: | 0.032 Inches Minimum And 0.042 Inches Maximum |
| Width Between Flats: | 0.0635 Inches Minimum And 0.0645 Inches Maximum |
| Shank Diameter: | 0.1370 Inches Minimum And 0.1375 Inches Maximum |
| Shank Style: | Pin-riquet, Straight, Threaded |
| Head Major Diameter: | 0.230 Inches Minimum And 0.235 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Grip Length: | 0.125 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.138 Inches |
| Shear Strength: | 2840 Double Pounds Per Square Inch |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Ams5737 Fed Spec Single Material Response Overall Or Ams5731 Fed Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this pin-riquet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL40-4-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.