

Description

protruding shear head, high temperature alloy, passivated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL4042
Minimum Qty (MOQ):	5
NSN:	5320-01-533-1097
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N HL40-4-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.419 Inches Nominal
Head Style:	Straight Pan
Head Height:	0.032 Inches Minimum And 0.042 Inches Maximum
Width Between Flats:	0.0635 Inches Minimum And 0.0645 Inches Maximum
Shank Diameter:	0.1370 Inches Minimum And 0.1375 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.230 Inches Minimum And 0.235 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.125 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Shear Strength:	2840 Double Pounds Per Square Inch
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5737 Fed Spec Single Material Response Overall Or Ams5731 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL40-4-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.