

**Description**

protruding shear head, high temperature alloy, passivated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL4042
Minimum Qty (MOQ):	5
NSN:	5320-01-533-1097
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N HL40-4-2 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.419 Inches Nominal
<b>Head Style:</b>	Straight Pan
<b>Head Height:</b>	0.032 Inches Minimum And 0.042 Inches Maximum
<b>Width Between Flats:</b>	0.0635 Inches Minimum And 0.0645 Inches Maximum
<b>Shank Diameter:</b>	0.1370 Inches Minimum And 0.1375 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.230 Inches Minimum And 0.235 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Grip Length:</b>	0.125 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.138 Inches
<b>Shear Strength:</b>	2840 Double Pounds Per Square Inch
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams5737 Fed Spec Single Material Response Overall Or Ams5731 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL40-4-2](https://military-fasteners.com/pins/pin_rivets/HL40-4-2) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.