

Description

protruding shear head, high temperature alloy, passivated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | HL4043 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-533-1095 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE
AVAILABLE

P/N HL40-4-3 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.4815 Inches Nominal |
| Head Style: | Straight Pan |
| Head Height: | 0.032 Inches Minimum And 0.042 Inches Maximum |
| Width Between Flats: | 0.0635 Inches Minimum And 0.0645 Inches Maximum |
| Shank Diameter: | 0.1370 Inches Minimum And 0.1375 Inches Maximum |
| Shank Style: | Pin-riquet, Straight, Threaded |
| Head Major Diameter: | 0.230 Inches Minimum And 0.235 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Grip Length: | 0.1875 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.138 Inches |
| Shear Strength: | 2840 Double Pounds Per Square Inch |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Ams5737 Fed Spec Single Material Response Overall Or Ams5731 Fed Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this pin-riquet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL40-4-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.