

Description

protruding shear head, a-286 high temperature alloy, passivated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[HL40-04-04](#)

SKU / Model:	HL4044
Minimum Qty (MOQ):	10
NSN:	5320-01-482-8133
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N HL40-4-4 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.534 Inches Minimum And 0.554 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.245 Inches Minimum And 0.255 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	1350 Newtons Per Square Millimeter
<b>Nominal Thread Size:</b>	0.138 Inches
<b>Shear Strength:</b>	4010 Double Pounds Per Square Inch
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL40-4-4](https://military-fasteners.com/pins/pin_rivets/HL40-4-4) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.