

Description

protruding shear head, a-286 high temperature alloy, passivated


* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[HL40-04-04](#)

SKU / Model:	HL4044
Minimum Qty (MOQ):	10
NSN:	5320-01-482-8133
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N HL40-4-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.534 Inches Minimum And 0.554 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.245 Inches Minimum And 0.255 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	1350 Newtons Per Square Millimeter
Nominal Thread Size:	0.138 Inches
Shear Strength:	4010 Double Pounds Per Square Inch
Thread Series Designator:	Unjc

How to Order

Order this pin-rievet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL40-4-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.