

Description

protruding shear head - a-286 high temperature alloy - passivated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | HL4045 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-482-8134 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N HL40-4-5 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.940 Inches Minimum And 0.960 Inches Maximum |
| Lubrication: | Cetyl Alcohol |
| Grip Length: | 0.307 Inches Minimum And 0.317 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 1350 Newtons Per Square Millimeter |
| Nominal Thread Size: | 0.138 Inches |
| Shear Strength: | 4010 Double Pounds Per Square Inch |
| Thread Series Designator: | Unjc |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL40-4-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.