

**Description**

protruding shear head - a-286 high temperature alloy - passivated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL4045
Minimum Qty (MOQ):	10
NSN:	5320-01-482-8134
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N HL40-4-5 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.940 Inches Minimum And 0.960 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.307 Inches Minimum And 0.317 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	1350 Newtons Per Square Millimeter
<b>Nominal Thread Size:</b>	0.138 Inches
<b>Shear Strength:</b>	4010 Double Pounds Per Square Inch
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL40-4-5](https://military-fasteners.com/rivets/pin_rivets/HL40-4-5) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.