

Description

Thread Size: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL40512
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-417-1031
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HL40-5-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.052 Inches Minimum And 1.072 Inches Maximum
Head Style:	Err-090
Head Height:	0.037 Inches Minimum And 0.047 Inches Maximum
Width Between Flats:	0.0791 Inches Minimum And 0.0801 Inches Maximum
Shank Diameter:	0.1630 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.242 Inches Minimum And 0.262 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.745 Inches Minimum And 0.755 Inches Maximum
Minimum Tensile Strength:	1940 Pounds Per Square Inch
Nominal Thread Size:	0.164 Inches
Shear Strength:	4010 Single Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjc

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL40-5-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.