

**Description**

Fastener Length: 29/64", Thread Size: 5/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL4052
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-288-3608
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE  
AVAILABLE

## P/N HL40-5-2 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.437 Inches Minimum And 0.457 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.037 Inches Minimum And 0.047 Inches Maximum
<b>Width Between Flats:</b>	0.079 Inches Minimum And 0.080 Inches Maximum
<b>Shank Diameter:</b>	0.1630 Inches Minimum And 0.1635 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.242 Inches Minimum And 0.262 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>End Item Identification:</b>	Aircraft, Hercules C-130, Aircraft, Eagle F-15 Helicopter Observation (ahip), Oh-58d, Aircraft, Galaxy C-5,joint Stars Target,aircraft, Harrier Av-8b,aircraft, Sof ( Ac-130h, Mc-130h, Ec-130e, Hc-130),aircraft, Hornet F/a-18, Aircraft, Phantom F-4,aircraft, F-16
<b>Grip Length:</b>	0.130 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5731 Assn Std 1st Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	258,fscm 73197 Mfr Ref Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL40-5-2](https://military-fasteners.com/rivets/pin_rivets/HL40-5-2) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.