

Description

Fastener Length: 29/64", Thread Size: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL4052
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-288-3608
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

P/N HL40-5-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.437 Inches Minimum And 0.457 Inches Maximum
Head Style:	Err-090
Head Height:	0.037 Inches Minimum And 0.047 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.080 Inches Maximum
Shank Diameter:	0.1630 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.242 Inches Minimum And 0.262 Inches Maximum
Lubrication:	Cetyl Alcohol
End Item Identification:	Aircraft, Hercules C-130, Aircraft, Eagle F-15 Helicopter Observation (ahip), Oh-58d, Aircraft, Galaxy C-5,joint Stars Target,aircraft, Harrier Av-8b,aircraft, Sof (Ac-130h, Mc-130h, Ec-130e, Hc-130),aircraft, Hornet F/a-18, Aircraft, Phantom F-4,aircraft, F-16
Grip Length:	0.130 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std 1st Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	258,fscm 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL40-5-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.