

Description

Fastener Length: 1/2", Thread Size: 11/64",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL4053
Minimum Qty (MOQ):	20
NSN:	5320-00-317-0791
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N HL40-5-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.495 Inches Minimum And 0.515 Inches Maximum
Head Style:	Err-090
Head Height:	0.037 Inches Minimum And 0.047 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.080 Inches Maximum
Shank Diameter:	0.1630 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Pin-riivet, Straight, Threaded
Head Major Diameter:	0.242 Inches Minimum And 0.262 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.193 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	258,fscm 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-riivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL40-5-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.