

P/N HL40-5-5

Description

HL40-5-5 Pin-Rivet

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: HL4055

Minimum Qty (MOQ):

NSN: 5320-01-600-0540

Schedule B: 7318.24.0000

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N HL40-5-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.624 Inches Nominal
Head Style:	Straight Pan
Head Height:	0.037 Inches Minimum And 0.047 Inches Maximum
Shank Diameter:	0.1630 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.242 Inches Minimum And 0.282 Inches Maximum
Grip Length:	0.125 Inches Nominal
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL40-5-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/pins/pin_rivets/HL40-5-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/pins/pin_rivets/HL40-5-5 and selecting the quantity you want then click "add to cart".