

**Description**


protruding shear head - a-286 high temperature alloy - passivated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL4058
Minimum Qty (MOQ):	5
NSN:	5320-01-216-2851
National Motor Freight:	105000, Dowel Pins I / S Noi In Bag / Bbl / Boxes



\* See page 2 for technical characteristics

## P/N HL40-5-8 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.802 Inches Minimum And 0.822 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.037 Inches Minimum And 0.047 Inches Maximum
<b>Width Between Flats:</b>	0.080 Inches Nominal
<b>Shank Diameter:</b>	0.163 Inches Nominal
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.242 Inches Minimum And 0.262 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.495 Inches Minimum And 0.505 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Special Features:</b>	Heat Treat: 95,000 Psi Shear Min At 70 Deg F
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall Or Ams 5731 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL40-5-8](https://military-fasteners.com/rivets/pin_rivets/HL40-5-8) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.