

Description


Fastener Length: 37/64", Thread Size: 3/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL4064
Minimum Qty (MOQ):	20
NSN:	5320-00-613-7957
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N HL40-6-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.565 Inches Minimum And 0.585 Inches Maximum
Head Style:	Err-090
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.189 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
End Item Identification:	Wsd: Aircraft, Orion P-3; Aircraft, Eagle F-15; Aircraft, Stratolifter C-135; Support Equipment, C-5 Aircraft; Joint Stars Target Radar System; Landing Craft Air Cushion (Lcac); Marine Hardware & Hull Doors; Aircraft, B-1b; Aircraft, Sof (ac-130h, Mc-130h, Ec-130e, Hc-130); Aircraft, Harrier Av-8b
Grip Length:	0.255 Inches Maximum
Nominal Thread Size:	0.190 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Criticality Code Justification:	Feat
Special Features:	Weapon System Essential
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall Or Ams 5731 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	258,fscm 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL40-6-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.