

Description

Fastener Length: 11/16", Thread Size: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL4068
Minimum Qty (MOQ):	15 EA
NSN:	5320-00-382-6200
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HL40-6-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Head Style:	Err-090
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
Lubrication:	Cetyl Alcohol
End Item Identification:	W/s: Aircraft, B-2 Bomber (atb); Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Aircraft, Eagle F-15; Aircraft, Harrier Av-8b; Engine, Aircraft J-52; Aircraft, Galaxy C-5
Grip Length:	0.510 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 57b7 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	258,fscm 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL40-6-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.