

## P/N HL40-8-6

## **Description**

Fastener Length: 49/64", Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: HL4086

Minimum Qty (MOQ): 10 EA

NSN: 5320-00-494-7991

Schedule B: 7318.24.0000

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N HL40-8-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.7600 Inches Minimum And 0.7800 Inches Maximum
Head Style:	Err-090
Head Height:	0.0590 Inches Minimum And 0.0690 Inches Maximum
Width Between Flats:	0.09470 Inches Minimum And 0.09670 Inches Maximum
Shank Diameter:	0.2797 Inches Minimum And 0.2807 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.3870 Inches Minimum And 0.4120 Inches Maximum
Grip Length:	0.3700 Inches Minimum And 0.3800 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.2500 Inches
Material:	Steel Comp 4130 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp E4340 Overall
Material Document And	Mil-s-6758 Mil Spec Single Material Response Overall Or Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec
Classification:	Single Material Response Overall Or Mil-s-5000 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty 2, Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/pin\_rivets/HL40-8-6">https://military-fasteners.com/rivets/pin\_rivets/HL40-8-6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.