

Description

Fastener Length: 57/64", Thread Size: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | HL4088 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5320-00-399-1134 |
| Schedule B: | 7318.24.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N HL40-8-8 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.885 Inches Minimum And 0.905 Inches Maximum |
| Head Style: | Err-090 |
| Head Height: | 0.059 Inches Minimum And 0.069 Inches Maximum |
| Width Between Flats: | 0.0947 Inches Minimum And 0.0967 Inches Maximum |
| Shank Diameter: | 0.2490 Inches Minimum And 0.2495 Inches Maximum |
| Head Major Diameter: | 0.387 Inches Minimum And 0.412 Inches Maximum |
| Lubrication: | Cetyl Alcohol |
| Grip Length: | 0.505 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.250 Inches |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | 258,fscm 73197 Mfr Ref Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL40-8-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.