

Description

Fastener Length: 27/64", Thread Size: 1/8", HL41 series pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL4142
Minimum Qty (MOQ):	20
NSN:	5320-01-160-2861
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	105000, Dowel Pins I / S Noi In Bag / Bbl / Boxes



* See page 2 for technical characteristics

P/N HL41-4-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.405 Inches Minimum And 0.425 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0635 Inches Minimum And 0.0645 Inches Maximum
Shank Diameter:	0.1370 Inches Minimum And 0.1375 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.2171 Inches Minimum And 0.2219 Inches Maximum
Grip Length:	0.120 Inches Minimum And 0.130 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Criticality Code Justification:	Aazg And Aaze And Aatb
Material:	Steel Overall
Material Document And Classification:	Ams 5737 Assn Std 1st Material Response Overall Or Ams 5731 Assn Std 2nd Material Response Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL41-4-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.