

P/N HL41-4-2

Military-Fasteners.com

Description

Fastener Length: 27/64", Thread Size: 1/8", HL41 series pin

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | HL4142 |
|-------------------------|---|
| Minimum Qty (MOQ): | 20 |
| NSN: | 5320-01-160-2861 |
| Schedule B: | 7318.24.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 105000, Dowel Pins I / S Noi In Bag / Bbl / Boxes |



P/N HL41-4-2 Specifications

| Thread Class: | 3a |
|---------------------------------------|--|
| Thread Direction: | Right-hand |
| Fastener Length: | 0.405 Inches Minimum And 0.425 Inches Maximum |
| Head Style: | Flush Countersunk |
| Width Between Flats: | 0.0635 Inches Minimum And 0.0645 Inches Maximum |
| Shank Diameter: | 0.1370 Inches Minimum And 0.1375 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.2171 Inches Minimum And 0.2219 Inches Maximum |
| Grip Length: | 0.120 Inches Minimum And 0.130 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.138 Inches |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Criticality Code Justification: | Aazg And Aaze And Aatb |
| Material: | Steel Overall |
| Material Document And Classification: | Ams 5737 Assn Std 1st Material Response Overall Or Ams 5731 Assn Std 2nd Material Response Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this pin-rivet from our inventory online by visiting <u>https://military-fasteners.com/pins/pin_rivets/HL41-4-2</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.