

Description

Diameter: 5/32", Grip Length: 3/16", flush shear head, high temperature alloy, passivated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |                             |
|-------------------------|-----------------------------|
| SKU / Model:            | HL4153                      |
| Minimum Qty (MOQ):      | 10                          |
| NSN:                    | 5320-00-288-3491            |
| ECCN:                   | EAR99                       |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



\* See page 2 for technical characteristics

## P/N HL41-5-3 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Fastener Length:</b>                               | 0.490 Inches Minimum And 0.510 Inches Maximum  |
| <b>Head Style:</b>                                    | Flush Countersunk  |
| <b>Width Between Flats:</b>                           | 0.079 Inches Minimum And 0.080 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.1630 Inches Minimum And 0.1635 Inches Maximum  |
| <b>Shank Style:</b>                                   | Pin-rivet, Straight, Threaded  |
| <b>Head Major Diameter:</b>                           | 0.256 Inches Minimum And 0.261 Inches Maximum  |
| <b>Lubrication:</b>                                   | Cetyl Alcohol  |
| <b>Grip Length:</b>                                   | 0.193 Inches Maximum   |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Nominal Thread Size:</b>                           | 0.164 Inches   |
| <b>Shear Strength:</b>                                | 95000 Single Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                             | 100.0 Degrees Nominal  |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Overall Or Ams 5731 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | 258,fscm 73197 Mfr Ref Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjc   |

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL41-5-3](https://military-fasteners.com/pins/pin_rivets/HL41-5-3) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.