

Description

Fastener Length: 45/64", Thread Size: 3/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL4166
Minimum Qty (MOQ):	10
NSN:	5320-00-291-5440
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HL41-6-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.690 Inches Minimum And 0.710 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.079 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.297 Inches Minimum And 0.302 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.380 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall Or Ams 5731 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	258,fscm 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL41-6-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.